

Motoréducteur 1.13.021/PM32

maxon



Versions produits					
SKU	Version	Tension nominale	Vitesse nominale	Couple nominal	Courant nominal
570497	12v/0003	12 V	810 tr/mn	59 mNm	0.9 A
570498	12v/0019	12 V	160 tr/mn	290 mNm	0.9 A
570499	12v/0168	12 V	18 tr/mn	2400 mNm	0.9 A
570500	12v/0397	12 V	7.6 tr/mn	4500 mNm	0.9 A
570501	24v/0003	24 V	810 tr/mn	59 mNm	0.5 A
570502	24v/0019	24 V	160 tr/mn	290 mNm	0.5 A
570503	24v/0034	24 V	86 tr/mn	520 mNm	0.5 A
570504	24v/0050	24 V	59 tr/mn	710 mNm	0.5 A
570505	24v/0092	24 V	32 tr/mn	1300 mNm	0.5 A
570506	24v/0168	24 V	18 tr/mn	2400 mNm	0.5 A
570507	24v/0291	24 V	10 tr/mn	3800 mNm	0.5 A
570508	24v/0397	24 V	7.6 tr/mn	4500 mNm	0.5 A
577302	12v/0092	12 V	32 tr/mn	1300 mNm	0.9 A
577303	12v/0050	12 V	59 tr/mn	710 mNm	0.9 A
577304	12v/0034	12 V	86 tr/mn	520 mNm	0.9 A
577305	12v/0291	12 V	10 tr/mn	3800 mNm	0.9 A

maxon

Gamme multitechnologique de maxon France

www.maxon-France.com ■ contact.fr@maxongroup.com ■ +33 (0)4 72 01 83 00

Type de commutation	Balais graphite	Force de chassage axiale max. (statique)	40 N
Matière des aimants	Ferrite		
Vitesse maximale admissible	7.6 tr/mn		